




G&G 2.0 MP IR Dome IP CCTV with POE - GIRDNS200



Key Features

- ✓ Vandal proof IR Dome Camera
- ✓ 1/3" SONY Low Illumination CMOS Sensor
- ✓ 3.6mm 2MP HD board Lens
- ✓ HISILICON Hi3518C Chipset
- ✓ Main Stream: 1080P/960P/720P@25fps,,
- ✓ Wide Dynamic Range
- ✓ Built in External POE
- ✓ IR LED: 14 μ x 18PCS
- ✓ IR range: 20M With IR-CUT



Model NO.	GIRDNS200
Camera	
Image Sensor	IMX222
Main processor	HI3518C
Resolution	1080p
Effective Pixels	1920(H)*1080(V)
Compression	H.264/JPEG/AVI/MJPEG
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Focus Length	3.6mm
Focus Control	Fixed
Pixels	3MP
Night Vision	
Infrared LED	14μ x 18PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	1920*1080@30fps
Sub Stream 1	704*576@30fps, 352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Defog Mode	Support
ROI	Support
BLC	Support
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands
General	
Housing	Metal, IP66
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	Φ 94.5 x 76(H) mm
Weight	450g

